

Euro+

6 chambers, profile depth 70 mm

Created for window manufacturers who export their products to Western European countries. It has all the profiles needed for use in historic buildings where window replacement is necessary.

0,84 $\frac{U_w}{W/m^2K}$ *

*for the reference window width 1,230 mm, height 1480 mm with, lase package of 44 mm/ Ug=0.6W/m2K and spacer bar Swisspacer V

decco[®]
E X T R U S I O N



DECCO EURO+

www.decco.eu

84 MD

AMERICAN SYSTEMS

SHUTTERS

62

71

82

83

EURO+

HST

SLIDE

65

AQUATHERM



2 seal profile

EURO+ system has 2 seals and 6 chambers with excellent thermal and acoustic properties. It is designed for window manufacturers who export their products to Western European countries. It has all the profiles required for use in historic buildings where window replacement is necessary.

- Decco Euro+ profiles designed for the production of windows dedicated to different European markets
- Two types of renovation subframes,
- „French window” system - with handle in the middle of the assembly with sash stop
- Ledges embedded in traditional subframes and renovation subframes
- Additional system components: narrow movable pillar, drip on the sash
- Masking profiles in different sizes: flat bars, angle bars, chamber slats
- The core of the profile matching the color of decorative foils.
- Seals in gray or black
- A wide range of decorative foils

Profile available in a wide range of colour and wood-imitating veneers



Nut 5

Golden Oak 8

Mahagony 9

Quartz Grey sand 61

Winchester XA 76

Woodec Sheffield Oak 1402

Woodec Turner Oak 1401

Black Ulti-Matt 504700

Silver Slate 86

Coal Grey sand 62

Colours close to original due to print technology

and many others

$$U_w = 0,84 [W/m^2K]^*$$

*for the reference window width 1,230 mm, height 1480 mm with, lass package of 44 mm / Ug=0.6W/m²K and spacer bar Swisspacer V